

LA-UR-18-27425

Approved for public release; distribution is unlimited.

Title: Troubleshooting and Analyzing Network Booting Challenges Using a Raspberry Pi Testbed

Author(s): Lapid, Maria Francine Therese Ruiz
Steen, Trent David
Schild, Christoph Victor

Intended for: HPC Mini-Showcase

Issued: 2018-08-06

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Troubleshooting and Analyzing Network Booting Challenges Using a Raspberry Pi Testbed

“Testing on the largest Raspberry Pi cluster in the world!”

Maria Francine Lapid
Christoph Schild
Trent Steen

Mentors:
Paul Peltz
J. Lowell Wofford



Introduction

- Background
- Testing environment
 - Hardware setup
 - Network setup
- Image distribution using Kraken
- Internet Small Computer System Interface (iSCSI)
 - What it's used for
 - What we found
- Future work


Background

LANL operates some of the world's fastest clusters.


But...

- The lab can't do scalability tests because those computers are necessary for research
- HPC developers need an inexpensive way to do systems testing

Hence the Raspberry Pi cluster!



Testing Environment: Hardware Setup



- Each chassis has 150 Pis and 3 internal switches
- We have different types of links between switches and devices
 - Might be a cause of bottlenecks
- Raspberry Pis are hardwired to the Power Controller Pi, which allows remote power cycling

Testing Environment: Network Setup

- Resolving conflicts requires network isolation
- Compute Pis are on separate subnet
- Each chassis is fed by a 10 Gb link





Image Distribution

- Working with Raspberry Pis poses a series of challenges
 - Not compatible with existing systems
 - Doesn't follow standardized protocols (DHCP Handshake)
 - "Node scan" must be done manually
- Kraken solves this
 - Created in-house in Go
 - Works with oddities of Raspberry Pis (custom DHCP)
 - Includes many microservices for distribution

Our Contributions to Kraken

We contributed a few pieces of software to Kraken:

- “Nodescan” for acquiring MAC addresses
 - Listens for DHCP DISCOVER traffic
 - Builds JSON for Kraken
- “Power Cycler” for assisting in the boot process of the Pis
 - Attempts to boot as many Pis as possible through repeated, timed reboots
- Automation Scripts for data retrieval from Pis
 - PSSH, Bash Scripting, and file parsing


iSCSI Intro

- Internet Small Computer System Interface
- Networking storage using IP
- Enables nodes to send SCSI commands over network and see external storage as internal
- Clients = Initiators, Server = Target
- Tested scalability using IOzone filesystem benchmark
 - Interested in the “read” tests (ie, sending out an OS image)
 - Varied file size and record length


iozone Filesystem Benchmark, www.iozone.org/.

iSCSI Test Results: Single Pi

- File size vs record length
- Mostly for comparison
- Record length has a bigger impact than file size
- Tends to slow down at file size 4 MB and record length 32 kB




iSCSI Test Results: 100 Pis (Averages)



- Slower than Single Pi test
- iSCSI is less efficient when running many small block operations
- iSCSI performs well with larger files and larger blocks
- File size and record length seem to both have effects on read speed

iSCSI Test Results: 100 Pis (Standard Deviations)

- Variation increases with record length
 - Less consistent
- High variation shows that we stressed system



Future Work

- Test other block storage methods
- Fix scalability issues, to push storage technologies further
 - Further stress block storage systems
- Eliminate unrelated bottlenecks by exploring other configuration
 - More accurate testing

Conclusion

We believe that the Raspberry Pi cluster is a sound testbed for scalability tests.

Thanks for Listening

Francine Lapid
Texas A&M University
mail@francinelapid.com



Christoph Schild
Northern Arizona University
chris@schild.tech



Trent Steen
Dakota State University
hi@trentsteen.com

